



# QM INDUSTRIES BEARING LIMITED



YET 204 Bearing 2D drawings and 3D CAD models

20 mm x 47 mm x 21 mm SKF YET 204 CHINA  
Bearing 20X47X30.5

Bearing No. YET 204

Category	Insert Bearings Spherical OD
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0.18
EAN	7316577029300
Product Group	M06110
Inner Race Profile	Narrow Inner Ring
Outer Race Profile	Spherical
Relubricatable	Yes
Seal Type	M Seal
Mounting Method	Eccentric Collar
Rolling Element	Ball Bearing
Snap Ring	No
Long Description	20MM Bore; Narrow Inner Ring; Ball Bearing; 31MM Length Thru Bore; 14MM Outer Race Width; 47MM Outside Diameter; Relubricatable; M Seal Seal; Eccentric Collar Mounting Method; No Snap Ring
Inch - Metric	Metric
Other Features	Single Row   Standard Duty   With Set Screw   Metric
Category	Insert Bearings
UNSPSC	31171536



## QM INDUSTRIES BEARING LIMITED

Harmonized Tariff Code	8482.10.50.00
Noun	Bearing
Keyword String	Insert
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	YET 204
Weight / LBS	0.397
Outer Race Width	0.551 Inch   14 Millimeter
D	1.85 Inch   47 Millimeter
D	1.22 Inch   31 Millimeter
d	0.787 Inch   20 Millimeter
bore diameter:	20 mm
radial dynamic load capacity:	12.7 kN
outside diameter:	47 mm
radial static load capacity:	6.55 kN
outer ring width:	14 mm
bearing material:	Stainless Steel
inner ring width:	31 mm
finish/coating:	Black Oxide
bore type:	Round
maximum rpm:	8500 RPM
locking device:	Eccentric Collar
series:	YET2
d	20 mm
D	47 mm
B <sub>1</sub>	30.5 mm
B	21 mm
C	14 mm
d <sub>1</sub>	28.2 mm
d <sub>2</sub>	32.4 mm
B <sub>4</sub>	4.75 mm
r <sub>1,2</sub> min.	0.6 mm
s <sub>1</sub>	23.5 mm



## QM INDUSTRIES BEARING LIMITED

Basic dynamic load rating C	12.7 kN
Basic static load rating $C_0$	6.55 kN
Fatigue load limit $P_u$	0.28 kN
Limiting speed <sup>1)</sup>	8500 r/min
Calculation factor $f_0$	13
Mass complete bearing	0.16 kg
Thread grub screw $G_2$	M6x0.75
Hexagonal key size for grub screw N	3 mm
Recommended tightening torque for grub screw	4 N · m
Rubber seating ring	RIS 204